

12500 TI Boulevard, MS 8640, Dallas, Texas 75243

Notification# 20160628009 Datasheet for LMV7219 Information Only

Date: 7/1/2016

To: TOKYO ELECTRON DEVICE (DSTR) PCN

Dear Customer:

This is an information-only announcement of a change to a device that is currently offered by Texas Instruments.

The changes discussed within this notification are for your information only.

Any negotiated alternative change requirements will be provided via the customer's defined process. Customers with previously negotiated, special requirements will be handled separately. Any inquiries should be directed to your local Field Sales Representative.

For questions regarding this notice, contact your local Field Sales Representative or the PCN Manager (PCN www admin team@list.ti.com).

Sincerely,

PCN Team SC Business Services

Information Only Attachments

Products Affected:

The devices listed on this page are a subset of the complete list of affected devices. According to our records, these are the devices that you have purchased within the past twenty-four (24) months. The corresponding customer part number is also listed, if available.

DEVICE LMV7219M5/NOPB LMV7219M7/NOPB **CUSTOMER PART NUMBER**

null null

Technical details of this Product Change follow on the next page(s).

	PCN Number: 20160628			009		PCN Date:		7/1/2016			
Title: Datasheet for LMV7219								., _,			
Customer Contact: PCN Manager			1		ept: Qua		lity Services				
Cha	nge Type:		·					•			
	Assembly Site		Desi	gn		Wafer	Bum	p Site			
	Assembly Process	S		Sheet			r Bump Material				
	Assembly Materials		Part	number change		Wafer	Wafer Bump Process				
	Mechanical Specification		Test	Site		Wafer	er Fab Site				
	Packing/Shipping/Labeling		Test	Process		Wafer	Wafer Fab Materials				
						Wafer Fab Process					
Notification Details											
	cription of Chan										
Texa	as Instruments Inc	corporated is a	announci	ng an information onl	y not	ificatio	n.				
The	following change Texas Instruments	history provid	les furthe					LMV7219			
_				SN	NOS458I -	-APRIL 200	0-REVIS	ED JUNE 2016			
Cha	anges from Revision H	(April 2016) to Rev	vision I					Page			
	Added Supports 105°C F	CB Temperature to	Added Supports 105°C PCB Temperature to Features List								
Changed Operating Temperature to Ambient Temperature											
•	Changed Operating Tem	perature to Ambien	nt Temperatu	re				4			
				re							
•	Added Junction Tempera Added PCB Temperature	ature of 125 °C e of 105 °C						4 4			
•	Added Junction Tempera Added PCB Temperature	ature of 125 °C e of 105 °C						4 4			
•	Added Junction Temperature Added PCB Temperature Added $T_{PCB} \le 105^{\circ}C$ thro	ature of 125 °C e of 105 °Coughout Electrical T	ables					4 4			
The	Added Junction Tempera Added PCB Temperature Added T _{PCB} ≤ 105°C thro datasheet numbe	ature of 125 °C e of 105 °Coughout Electrical T	ables					4 4 5			
The	Added Junction Tempera Added PCB Temperature Added T _{PCB} ≤ 105°C thro datasheet numbe vice Family	ature of 125 °C e of 105 °C oughout Electrical T	ging.	nge From:			Chan	4 4 			
The	Added Junction Tempera Added PCB Temperature Added T _{PCB} ≤ 105°C thro datasheet numbe	ature of 125 °C e of 105 °C oughout Electrical T	ging.				Chan	4 4 5			
The Dev	Added Junction Temperature Added PCB Temperature Added T _{PCB} ≤ 105°C thro datasheet numbe vice Family V7219	e of 105 °C e of 105 °C bughout Electrical T r will be change e reviewed at	ging. Cha SNO	nge From:			Chan	4 4 			
The Dev LM'	Added Junction Temperature Added PCB Temperature Added T _{PCB} ≤ 105°C thro datasheet numbe vice Family V7219 se changes may b	e reviewed at	ging. Cha SNO	nge From:)S458H			Chan	4 4 5 ge To:			
The Dev LM' These http	Added Junction Temperature Added PCB Temperature Added T _{PCB} ≤ 105°C thro datasheet numbe vice Family V7219 se changes may b ://www.ti.com/pre	e reviewed at	ging. Cha SNC the data	nge From: 0S458H sheet links provided.			Chan	4 4 5 ge To:			
The Dev LM' These http	Added Junction Temperature Added PCB Temperature Added T _{PCB} ≤ 105°C thro datasheet numbe vice Family V7219 se changes may b ://www.ti.com/pre son for Change: nore accurately re	e of 105 °C Toughout Electrical Tough	ging. Cha SNC the data	nge From: 0S458H sheet links provided.			Chan	ge To: S458I			
The Dev LM' These http Rea To n Anti	Added Junction Temperature Added PCB Temperature Added T _{PCB} ≤ 105°C thro datasheet numbe vice Family V7219 se changes may b ://www.ti.com/pre son for Change: nore accurately re icipated impact	e reviewed at oduct/LMV721	ging. Cha SNO the data 9	nge From: 0S458H sheet links provided.	oility	(posit	Chan SNO:	ge To: 5458I negative):			
The Dev LM' Theshttp Rea To n Anti	Added Junction Temperature Added PCB Temperature Added T _{PCB} ≤ 105°C thro datasheet numbe vice Family V7219 se changes may b ://www.ti.com/pre son for Change: nore accurately re icipated impact anticipated impact anticipated impact ne actual device.	e reviewed at oduct/LMV721 flect device change. This is a spe	ging. Cha SNC the data 9 naracteris	nge From: 0S458H sheet links provided. stics. on, Quality or Relial	oility	(posit	Chan SNO:	ge To: 5458I negative):			
The Dev LM' These http Rea To n Anti No a to th	Added Junction Temperal Added PCB Temperature Added T _{PCB} ≤ 105°C throw datasheet number vice Family V7219 See changes may be ://www.ti.com/proson for Change: nore accurately resicipated impact anticipated impact actual device. Index of the product of the p	e reviewed at oduct/LMV721 flect device change. This is a spe	ging. Cha SNC the data 9 naracteris	nge From: 0S458H sheet links provided. stics. on, Quality or Reliate change announceme	oility	(posit	Chan SNO:	ge To: 5458I negative):			
The Dev LM' These http Rea To no Anti No a to the Cha	Added Junction Temperal Added PCB Temperature Added T _{PCB} ≤ 105°C throw datasheet number vice Family V7219 See changes may be ://www.ti.com/proson for Change: nore accurately resicipated impact anticipated impact actual device. Index of the product of the p	e reviewed at oduct/LMV721 flect device change. This is a spe	ging. Cha SNC the data 9 naracteris	nge From: 0S458H sheet links provided. stics. on, Quality or Reliate change announceme	oility	(posit	Chan SNO:	ge To: 5458I negative):			
The Dev LM' These http Rea To n Anti No a to th Cha None	Added Junction Temperature Added PCB Temperature Added T _{PCB} ≤ 105°C thro datasheet numbe vice Family V7219 se changes may b ://www.ti.com/pre son for Change: nore accurately re icipated impact enticipated impact entic	e reviewed at oduct/LMV721 flect device change. This is a spe	the data 9 naracteris	nge From: 0S458H sheet links provided. stics. on, Quality or Reliate change announceme	Dility nt on	(posit	Chan SNO:	ge To: 5 4 7 negative):			

For questions regarding this notice, e-mails can be sent to the regional contacts shown below or your local Field Sales Representative.

Location	E-Mail
USA	PCNAmericasContact@list.ti.com
Europe	PCNEuropeContact@list.ti.com
Asia Pacific	PCNAsiaContact@list.ti.com
Japan	PCNJapanContact@list.ti.com