

#### 12500 TI Boulevard, MS 8640, Dallas, Texas 75243

# PCN#20230501000.1 Qualify TI Mexico as an additional Assembly site for select devices Change Notification / Sample Request

**Date:** May 03, 2023

To: TOKYO ELECTRON DEVICE (DSTR) PCN

#### Dear Customer:

This is an announcement of a change to a device that is currently offered by Texas Instruments. The details of this change are on the following pages.

Texas Instruments requires acknowledgement of receipt of this notification within **30** days of the date of this notice. Lack of acknowledgement of this notice within 30 days constitutes acceptance of the change. If samples or additional data are required, requests must be received within **30 days** of this notification.

The changes discussed within this PCN will not take effect any earlier than the proposed first ship date on Page 3 of this notification, unless customer agreement has been reached on an earlier implementation of the change.

This notice does not change the end-of-life status of any product. Should product affected be on a previously issued product withdrawal/discontinuance notice, this notification does not extend the life of that product or change the life time buy offering/discontinuance plan.

For questions regarding this notice or to provide acknowledgement of this PCN, you may contact your local Field Sales Representative or the PCN Team (PCN www admin team@list.ti.com). For sample requests or sample related questions, contact your local Field Sales Representative.

Sincerely,

PCN Team SC Business Services

## 20230501000.1 Attachment: 1

## **Products Affected:**

The devices listed on this page are a subset of the complete list of affected devices. According to our records, these are the devices that you have purchased within the past twenty-four (24) months. The corresponding customer part number is also listed, if available.

DEVICE	<b>CUSTOMER PART NUMBER</b>
LMR23610ADDA	null
TPS54540DDA	null
TPS54540DDAR	null
LMR23610ADDAR	null
LMR23630ADDA	null
TPS54340DDA	null
TPS54340DDAR	null
TPS54360DDAR	null
TPS54560DDA	null
LMR23630ADDAR	null
LMR23630AFDDAR	null
TPS54340BDDA	null
TPS54340BDDAR	null
TPS54360BDDAR	null
TPS54560DDAR	null
LMR23630AFDDA	null
TPS54360DDA	null
LMR23625CDDAR	null
TPS54560BDDA	null

Technical details of this Product Change follow on the next page(s).

PCN Nui	<b>PCN Number:</b> 20230501000.1				. 1			PC	N Date:	May 03, 2023	
Title:	Title: Qualify TI Mexico as an additional Assembly site for select devices										
Custome	er Contact:	P	CN Manager			Dept:	Quality Se	ervic	es		
Propose Date:	d 1 <sup>st</sup> Ship		Aug 02, 2	202	3	Sample requests accepted until:				June 02, 2023*	
*Sample	requests rece	iv	ed after Ju	ne	02, 2	023 will no	t be suppo	rted	•		
Change	Туре:										
Asse	mbly Site				Design				Wafer Bump Material		
Asse	embly Process				Data	a Sheet 🔲 Wafer B			Wafer Bu	mp Process	
Asse	mbly Materials	S			Part	rt number change			Wafer Fab Site		
Mec	hanical Specifi	ca	ition		Test	Site			Wafer Fal	Wafer Fab Materials	
□ Packing/Shipping/Labeling □ Test				Test Process		Wafer Fab Process					
	PCN Details										
Descript	ion of Chang	e:									

Texas Instruments is pleased to announce the qualification of TI Mexico as an additional Assembly site for the list of devices shown below. Material differences between sites as follows.

Assembly Site	Assembly Site Origin	Assembly Country Code	<b>Assembly City</b>
ASESH	ASH	CHN	Shanghai
TI Mexico	MEX	MEX	Aguascalientes

## **Material Differences:**

## **Group 1 device:**

	ASESH	TI Mexico
Mount compound	EY1000063	4147858
Mold Compound	EN2000509	4211880

## **Group 2 device:**

	ASESH	TI Mexico
Mount compound	EY1000102	4224264
Mold Compound	EN2000509	4211880

## Marking <u>Differences</u>:

g Differences.		
	ASESH	TI Mexico
Pin 1 ID	Stripe	Dot
ECAT (G4)	With	Remove
Exa mple	TI 15A PONJ <u>84</u>	LM5163 TI23M MAQCE

## **Reason for Change:**

Continuity of Supply

## Anticipated impact on Fit, Form, Function, Quality or Reliability (positive / negative):

None

#### **Impact on Environmental Ratings:**

Checked boxes indicate the status of environmental ratings following implementation of this change. If below boxes are checked, there are no changes to the associated environmental ratings.


RoHS	REACH	Green Status	IEC 62474
☑ No Change	☑ No Change	⊠ No Change	☑ No Change

## Changes to product identification resulting from this PCN:

Assembly Site		
ASESH	Assembly Site Origin (22L)	ASO: ASH
TI Mexico	Assembly Site Origin (22L)	ASO: MEX

Sample product shipping label (not actual product label)





(1P) \$N74L\$07N\$R (Q) 2000 (D) 0336 (31T)LOT: 3959047MLA (4W) TKY(1T) 7523483812 (P) (2P) REV: (V) 0033317

(2P) REV: (V) 0033317 (20L) CSO: SHE (21L) CCO:USA (22L) ASO: MLA (23L) ACO: MYS

#### **Product Affected**

#### **Group 1 Device**

or out a portion			
TPS54340BDDA	TPS54360BDDA	TPS54540BDDA	TPS54560BDDA
TPS54340BDDAR	TPS54360BDDAR	TPS54540BDDAR	TPS54560DDA
TPS54340DDA	TPS54360DDA	TPS54540DDA	TPS54560DDAR
TPS54340DDAR	TPS54360DDAR	TPS54540DDAR	

## **Group 2 Device**

LMR23610ADDA	LMR23625CDDAR	LMR23630ADDA	LMR23630AFDDAR
LMR23610ADDAR	LMR23625CFDDA	LMR23630ADDAR	
LMR23625CDDA	LMR23625CFDDAR	LMR23630AFDDA	

# **Group 1 Qualification Report**

Approve Date 19-Apr-2023

## **Qualification Results**

Data Displayed as: Number of lots / Total sample size / Total failed

Туре	#	Test Name	Condition	Duration	Qual Device: TPS54540DDAR	QBS Reference: LMR16020PDDAR	QBS Reference: LM5163DDAR	QBS Reference: LM5169FQDDARQ1
HAST	A2	Biased HAST	110C/85%RH	264 Hours	-	-	-	3/231/0
AC	A3	Autoclave	121C/15psig	96 Hours	-	3/231/0	3/231/0	-
UHAST	A3	Unbiased HAST	110C/85%RH	264 Hours	-	-	-	3/231/0
TC	A4	Temperature Cycle	-65C/150C	500 Cycles	-	3/231/0	3/231/0	3/231/0
HTSL	A6	High Temperature Storage Life	150C	1000 Hours	-	3/231/0	3/231/0	-
HTSL	A6	High Temperature Storage Life	175C	500 Hours	-	-	-	3/135/0
WBS	C1	Ball Shear	76 balls, 3 units min	Wires	3/228/0	3/228/0	3/228/0	3/90/0
WBP	C2	Bond Pull	76 Wires, 3 units min	Wires	3/228/0	3/228/0	3/228/0	3/90/0
SD	C3	PB-Free Solderability	Precondition w.155C Dry Bake (4 hrs +/- 15 minutes); PB- Free Solder;	-	-	-	3/66/0	1/15/0
PD	C4	Physical Dimensions	Cpk>1.67	-	3/15/0	3/15/0	3/15/0	3/30/0

CHAR	E5	Electrical Characterization	Per Datasheet Parameters	-	1/30/0	1/30/0	1/30/0	-
CHAR	E5	Electrical Distributions	Cpk>1.67 Room, hot, and cold	-	-	-	-	3/90/0

QBS: Qual By Similarity

Qual Device TPS54540DDAR is qualified at MSL2 260C

Preconditioning was performed for Autoclave, Unbiased HAST, THB/Biased HAST, Temperature Cycle, Thermal Shock, and HTSL, as applicable

The following are equivalent HTOL options based on an activation energy of 0.7eV: 125C/1k Hours, 140C/480 Hours, 150C/300 Hours, and 155C/240 Hours

The following are equivalent HTSL options based on an activation energy of  $0.7 \, \text{eV}$ :  $150 \, \text{C/1k}$  Hours, and  $170 \, \text{C/420}$  Hours

The following are equivalent Temp Cycle options per JESD47 : -55C/125C/700 Cycles and -65C/150C/500 Cycles Quality and Environmental data is available at Tl's external Web site: http://www.ti.com/

Green/Pb-free Status: Qualified Pb-Free(SMT) and Green

# **Group 2 Qualification Report**

Approve Date 19-Apr-2023

## **Qualification Results**

Data Displayed as: Number of lots / Total sample size / Total failed

Туре	#	Test Name	Condition	Duration	Qual Device: LMR23630AFDDAR	QBS Reference: LMR16020PDDAR	QBS Reference: LM5163DDAR	QBS Reference: LM5169FQDDARQ1
HAST	A2	Biased HAST	110C/85%RH	264 Hours	-	-	-	3/231/0
AC	A3	Autoclave	121C/15psig	96 Hours	3/231/0	3/231/0	3/231/0	-
UHAST	A3	Unbiased HAST	110C/85%RH	264 Hours	-	-	-	3/231/0
TC	A4	Temperature Cycle	-65C/150C	500 Cycles	3/231/0	3/231/0	3/231/0	3/231/0
HTSL	A6	High Temperature Storage Life	150C	1000 Hours	-	3/231/0	3/231/0	-
HTSL	A6	High Temperature Storage Life	175C	500 Hours	-	-	-	3/135/0
WBS	C1	Ball Shear	76 balls, 3 units min	Wires	3/228/0	3/228/0	3/228/0	3/90/0
WBP	C2	Bond Pull	76 Wires, 3 units min	Wires	3/228/0	3/228/0	3/228/0	3/90/0
SD	СЗ	PB-Free Solderability	Precondition w.155C Dry Bake (4 hrs +/- 15 minutes); PB- Free Solder;	-		-	3/66/0	1/15/0
PD	C4	Physical Dimensions	Cpk>1.67	-	3/15/0	3/15/0	3/15/0	3/30/0
CHAR	E5	Electrical Characterization	Per Datasheet Parameters	-	1/30/0	1/30/0	1/30/0	-
CHAR	E5	Electrical Distributions	Cpk>1.67 Room, hot, and cold	-	-	-	-	3/90/0

QBS: Qual By Similarity

Qual Device LMR23630AFDDAR is qualified at MSL2 260C

Preconditioning was performed for Autoclave, Unbiased HAST, THB/Biased HAST, Temperature Cycle, Thermal Shock, and HTSL, as applicable

The following are equivalent HTOL options based on an activation energy of 0.7eV: 125C/1k Hours, 140C/480 Hours, 150C/300 Hours, and 155C/240 Hours

The following are equivalent HTSL options based on an activation energy of 0.7eV: 150C/1k Hours, and 170C/420 Hours The following are equivalent Temp Cycle options per JESD47: -55C/125C/700 Cycles and -65C/150C/500 Cycles Quality and Environmental data is available at Tl's external Web site: http://www.ti.com/

Green/Pb-free Status: Qualified Pb-Free(SMT) and Green

For questions regarding this notice, e-mails can be sent to the regional contacts shown below or your local Field Sales Representative.

Location	E-Mail			
WW PCN Team	PCN www admin_team@list.ti.com			

## IMPORTANT NOTICE AND DISCLAIMER

TI PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATASHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with TI products. You are solely responsible for (1) selecting the appropriate TI products for your application, (2) designing, validating and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, or other requirements. These resources are subject to change without notice. TI grants you permission to use these resources only for development of an application that uses the TI products described in the resource. Other reproduction and display of these resources is prohibited. No license is granted to any other TI intellectual property right or to any third party intellectual property right. TI disclaims responsibility for, and you will fully indemnify TI and its representatives against, any claims, damages, costs, losses, and liabilities arising out of your use of these resources.

TI's products are provided subject to TI's Terms of Sale (<a href="www.ti.com/legal/termsofsale.html">www.ti.com/legal/termsofsale.html</a>) or other applicable terms available either on ti.com or provided in conjunction with such TI products. TI's provision of these resources does not expand or otherwise alter TI's applicable warranties or warranty disclaimers for TI products.